

# IXLOOKUP

## Description

Looks up index.

## Syntax

`bforward = IXLOOKUP (ctrlentID, ctrlclassID, indexedtable, searchcolumns, displaycolumns, selmode)`

## Parameters

IXLOOKUP accepts arguments for the following parameters.

Parameter	Description	
<code>ctrlentID</code>	Has the format <code>WindowName.ControlName</code> , where <code>WindowName</code> is the identifier of the window that contains the affected control, and <code>ControlName</code> is the identifier of the control. Notice that a period separates the two values.	
<code>ctrlclassID</code>	The type of control that recognizes the event. The window control is the only valid entry.	
<code>indexedtable</code>	The table containing Btree index(es).	
<code>searchcolumns</code>	The indexed columns to search delimited by @FM.	
<code>displaycolumns</code>	The columns to display in the resultant popup, delimited by @FM.	
<code>selmode</code>	The selection mode delimited by @FM.	
	Value	Description
	Field 1	MULTI or SINGLE. If null, then SINGLE.
	Field 2	Control to return popup result to. If null, then whatever control is specified. The default is QBFLIST.
	Field 3	Control property to set. Generally <a href="#">TEXT</a> .

## Returns

True or false. If false, the program execution returns to the calling procedure. If true, the event processing goes to the next level.

## See also

[QBFLIST](#) property