

Inet_Aborted Function

Description

Called when an INET procedure has crashed and the Internet Gateway recovers.

Syntax

Inet_Aborted(Request, ProcErr)

Caution: This procedure **MUST NOT** fail (i.e. go to the debugger) or the Internet Services Gateway will be halted or go into an infinite loop. The Gateway has no way to auto-recover from a failure in this procedure!

Remarks

The ProcErr parameter is passed to the Inet_Aborted routine from Run_OECGI_Request.

Note: The *Inet_Aborted* source code ships with *OpenInsight*. This code may be modified. It is recommended that a backup be kept of any changed *Revelation* source code because future releases of *OpenInsight* may overwrite this routine.

Example

This is the actual source code for the Inet_Aborted executable that ships with OpenInsight.

```
function INET_Aborted(Request, ProcErr)
*****
* Returns      : An HTML error message.
*****

$insert Logical
$insert Inet_Equates
$insert Msg_Equates
declare function INET_Msg
    if assigned(ProcErr) then
        convert \00\:@fm:@vm:@svm to @tm:@tm:@tm:@tm in ProcErr
    end else
        ProcErr = ''
    end
response = ''
response<MTEXT$> = 'Fatal error while processing| request':@tm:@tm:ProcErr
response<MCAPTION$> = 'OpenInsight -- Server Error'
return Inet_Msg('', response)
```