

MAPILogoff Function

Description

Ends a session with the MAPI messaging system.

Syntax

```
status = MAPILogoff(session[, parent])
```

Parameters

The MAPILogoff function has the following parameters.

Parameter	Description
session	Contains a MAPI session handle returned by MAPILogon.
parent	Contains the name of an OpenInsight parent window. If not specified any dialog box displayed will be application modal.

After the logoff function completes successfully the MAPI session handle will no longer be valid.

Returns

1 for successful execution or 0 for failure.

If function execution fails, you can retrieve a text error message by calling the Get_Status function. For example, to display an error message on the screen, include the following error handling routine in your code:

```
Get_Status(ErrMsg)
```

```
Msg(@window, ErrMsg)
```

See also

[Get_Status\(\)](#), [MAPILogon\(\)](#)

Example

```
Subroutine DemoMAPILogoff(var)
*      Logs on to MAPI and logs off
$INSERT MAPI_EQUATES
Declare Function MAPILogon, MAPILogoff
Declare Subroutine Msg, Get_Status
if MAPILogon(session) then
    if MAPILogoff(session) then
        Msg(@window, "Logon and logoff successful")
    end else
        Get_Status(display)
        Msg(@window, display)
    end
end else
    Get_Status(display)
    Msg(@window, display)
end
return
```