

DROPMOVE

Applies to

Drop Source controls

Description

A boolean property denoting if a drop source control allows a MOVE operation.

Usage

dropMove = **Get_Property** (*dropSource*, "DROPMOVE")

existingState = **Set_Property** (*dropSource*, "DROPMOVE", *bValue*)

Remarks

Values passed in Set_Property():

Value	Description
bValue	Boolean true (1) or false (0)

By default the DROPMOVE property is set to 1. If the Drag Source control does not allow a MOVE operation then setting this property to True will have no effect. OpenInsight will set this property before calling the DRAGOVER event based upon the restrictions of the Drag Source.

When overriding the default property of the Drop Target control, this property should be set during the DRAGOVER event.

Returns

Values returned by Get_Property and Set_Property

Value	Description
dropCopy	the Boolean status of the control's DROPMOVE.
existingState	the Boolean status of the control's DROPMOVE, when Set_Property was run.

See Also

[DROPSOURCE property](#), [DROPCOPY property](#), [DRAGMOVE property](#)

Example

```
Declare function Get_Property, Set_Property

* Turn the DROPMOVE property off on the Dragover event.

dropSource = Get_Property("SYSTEM", "DROPSOURCE")
dropMove = Set_Property(dropSource, "DROPMOVE", 0)
```