

# Write\_Row Routine

## Description

Writes one row to a specified table.

## Syntax

**Write\_Row** (*tablename, key, columnvaluelist, lockflag*)

## Parameters

The Write\_Row routine has the following parameter.

Parameter	Description	
<i>Tablename</i>	Specifies the name of the table to which to write a row.	
<i>Key</i>	The name of the key in tablename to which to write information.	
<i>columnvaluelist</i>	List of values to write to a row in tablename. Each value is written to a column. key and columnvaluelist create a row in the table.	
	<b>Lockflag</b>	<b>Description</b>
	0	No locking takes place.
	1	Row is locked prior to write and is unlocked immediately following.
	2	Row unlocked after write operation.

## See also

[Read\\_Row](#)

## Examples

```
/* Writes row 1 to the CAR_ORDERS table.
The ORDER_NUM is 30, the SUPP_NO is B10, the DATE_ORD is 10/20/90, and the TOTAL_PRICE is $23.50.
The row is unlocked after the write operation. */

columnvaluelist = "30":@FM:"B10":@FM:"10/20/90":@FM:"23.50"

Write_Row("CAR_ORDERS", "1", columnvaluelist, 2)

if Get_Status(ErrCodes) then
  GoSub ErrorHandling
end
```