

# DESTROY Service

## Description

Used to destroy an object. DESTROY is used by [End\\_Window\(\)](#) and [End\\_Dialog](#). If Utility ('DESTROY') is called, the window will be flagged for destruction rather than actually destroyed.

An OpenInsight application will close when the main application window closes. To close an OpenInsight application programmatically, use

```
retval = Utility("DESTROY", "SYSTEM")
```

**Note:** *This is a Windows only function.*

## Parameters

Parameter	Description
<object>	The qualified name of the object to destroy.
Returnvalue	True if the object was found and destroyed, false otherwise.

## See Also

Name
<a href="#">BEEP Service</a>
<a href="#">CHOOSECOLOR Service</a>
<a href="#">CHOOSEDIR Service</a>
<a href="#">CHOOSEFILE Service</a>
<a href="#">CHOOSEFONT Service</a>
<a href="#">COPYFILE Service</a>
<a href="#">CREATE Service</a>
<a href="#">CURSOR Service</a>
<a href="#">FLUSH Service</a>
<a href="#">GET_EVENT Service</a>
<a href="#">GETLOGICALDRIVES Service</a>
<a href="#">MAKEDIR Service</a>
<a href="#">OBJECTID Service</a>
<a href="#">OBJECTLIST Service</a>
<a href="#">PRINTSETUP Service</a>
<a href="#">REMOVEDIR Service</a>
<a href="#">RENAMEDIR Service</a>
<a href="#">RENAMEFILE Service</a>
<a href="#">RUNHELP Service</a>
<a href="#">RUNWIN Service</a>
<a href="#">TEXTRECT Service</a>
<a href="#">WINCOUNT Service</a>
<a href="#">HANDLE_BY_CURSOR Service</a>
<a href="#">IUNKNOWN_RELEASE Service</a>

LOAD_PICTURE Service
OBJECT_BY_CURSOR Service
PICTURE_PROPS Service