

Repository Function GETEVALUATE

Description

Method for getting the entity's evaluate flag and notes information.

Syntax

```
retval = Repository("GETEVALUATE", entID)
```

Parameters

The **GETEVALUATE** method has the following parameters.

Parameter	Description
Message	"GETEVALUATE"
entID	entID consists of four elements, which are '*' (asterisk) delimited: <ul style="list-style-type: none">• Application name• Type ID• Class ID• Entity name
	Methods are executed as follows: if class specific, execute at the class level; if type specific, execute at the type level; otherwise, execute the method.

Returns

Field 1 contains the evaluation flag for the entity. Field 2 contains notes for the entity, as stored in SYSREPOS.

Note: Always call the [Get_Status function](#) after calling Repository.

See also

[Repository\(\) function](#), [Get_Repos_Entities\(\)](#).

Example

```
/* Get the evaluation flag and notes for the CENTERWINDOW stored procedure into the variable called result */
Declare Function Get_Repos_Entities, Repository, Get_Status
AppID = @APPID<1> /* current application
TypeID = "STPROC" /* OpenInsight stored procedures
ClassID = "" /* Not Applicable
Stored_Proc_Name = 'CENTERWINDOW'
entid = AppID : '*' : TypeID : '*' : ClassID : '*' : Stored_Proc_Name
result = Repository("GETEVALUATE", entid)
/* result now contains the evaluate flag of CENTERWINDOW in Field 1 and notes for the entity in Field 2*/
If Get_Status(ErrCode) then
    call msg(@window, 'Error Message returned: ' : ErrCode)
end
```