

# RTI\_List Function

## Description

The RTI\_List function is a utility that helps in the use and management of saved lists in the SYSLISTS table.

## Syntax

```
returnvalue = RTI_List(<function>, <listID> [,<param1>][,<param2>][,<param3>][,<param4>])
```

## Parameters

The function has the following parameters:

Parameter	Description						
<i>function</i>	A valid RTI_List function: READ, DELETE.						
<i>listID</i>	Name of the saved list (or Key ID) in the SYSLISTS table.						
<i>param1...</i>	Each method has different parameter requirements.						
<i>param4</i>							
functions	<table border="1"><thead><tr><th>Value</th><th>Description</th></tr></thead><tbody><tr><td>READ</td><td>Reads all the Key IDs from the indicated saved list and returns them as an @FM delimited array.</td></tr><tr><td>DELETE</td><td>Deletes the indicated saved list.</td></tr></tbody></table>	Value	Description	READ	Reads all the Key IDs from the indicated saved list and returns them as an @FM delimited array.	DELETE	Deletes the indicated saved list.
Value	Description						
READ	Reads all the Key IDs from the indicated saved list and returns them as an @FM delimited array.						
DELETE	Deletes the indicated saved list.						
Parameters	<table border="1"><thead><tr><th>Function</th><th>Parameters</th></tr></thead><tbody><tr><td>READ</td><td><i>bAutoDelete</i> - Flag that determines if the saved list should be deleted automatically after the READ function is invoked.</td></tr><tr><td>DELETE</td><td>Null</td></tr></tbody></table>	Function	Parameters	READ	<i>bAutoDelete</i> - Flag that determines if the saved list should be deleted automatically after the READ function is invoked.	DELETE	Null
Function	Parameters						
READ	<i>bAutoDelete</i> - Flag that determines if the saved list should be deleted automatically after the READ function is invoked.						
DELETE	Null						

## Returns

Method	Return Value
READ	An @fm-delimited array of Key IDs.
DELETE	Null

## Examples

```
* READ Example
DECLARE FUNCTION RTI_LIST, RTI_CREATEGUID
myID = RTI_CREATEGUID("b") ;* MAKE A GUID IN BASE64 FORMAT
CALL RLIST(selStmt, 4, myID, "", "")
fullList = RTI_LIST("READ", myID)

* DELETE Example
CALL RTI_LIST("DELETE", myID)
```