

ApptField

A user defined field for a single appointment.

Version Introduced: 4.1

Usage

```
Set_Property(OLECtrlEntID, "OLE.ApptField[ID; FieldName]", Value)
```

Values

Any custom value.

Indices

Index	Description
ID	Unique ID of an existing appointment
FieldName	The name of the field whose value to get or set

Remarks

Every appointment can have custom fields associated with them. Think of it like the User Defined Property feature of OpenInsight. Instead of attaching custom data to a control, you can attach it to an individual appointment. This can make your code a lot cleaner by not having to maintain external lookup structures.

Use this property to set or get a single field for an individual appointment. You can name the field anything you want, but you cannot use . or ; characters. Getting this property returns the field's value or "" if the field doesn't exist.

Setting a field doesn't do anything visibly within the Schedule control. It's a convenient way to store additional data.

If you need to set several fields at once for an appointment, use the [ApptFields](#) property.

Example

```
// Set a field
Set_Property(@Window:".OLE_SCHEDULE", "OLE.ApptFlag[Appt0001;CustomerId]", "0012")

// Get a field
JobNum = Get_Property(@Window:".OLE_SCHEDULE", "OLE.ApptFlag[Appt0001;JobNum]")
```

See Also

[ApptFields](#)