

Database_Services

C	
CalculateColumn	Called directly from within a calculation column.
ClearTableHandle	Clears the table handle array array from cache.
D	
DeleteDataRow	Deletes a data row for the indicated Key ID and database table.
G	
GetKeyIDLock	Attempts to perform a semaphore lock on the indicated tablename and Key ID.
GetTableCommuter	Returns the name of the indicated table's commuter module if it exists.
GetTableHandle	Returns an array of information related to the database table being passed in.
GetTableProperties	Returns an array of information related to the database table being passed in.
GetUserLocks	Returns a dynamic array of user lock information.
I	
IsKeyIDLocked	Returns a Boolean flag of the lock status for the indicated table and Key ID.
IsKeyIDSelfLocked	Returns a Boolean flag of the self-lock status for the indicated table and Key ID.
R	
ReadDataRow	Reads a data row for the indicated Key ID and database table.
ReleaseKeyIDLock	Attempts to release a semaphore lock on the indicated tablename and Key ID.
S	
SetTableAlias	Attempts to create an alias for the indicated table, volume, and database.
SearchIndex	Returns an @FM delimited list of Key IDs that match the search value.
U	
UnlockKeyID	Attempts to unlock the indicated Key ID from the indicated Table Name. Note, this can only be done with the UD 5.
V	
VerifyLH	Performs a health check against the indicated tables and returns back any issues.
VerifyLHAll	Performs a health check against all attached tables and returns back any issues.
W	
WriteDataRow	Writes a data row for the indicated Key ID and database table.