

SetDayStyles

Sets any number of dates and date ranges to the same visual style.

Syntax

```
rv = Send_Message(Ctrl, "OLE.SetDayStyles", Style, Days)
```

Parameters

Parameter	Description
Style	The new style to be applied to the given days
Days	An @FM delimited list of dates and date ranges that will receive the new style

Remarks

The SetDayStyle method is a convenient way of setting the visual style of any number of dates and date ranges. The Style parameter uses the same multivalue structure as the [DayStyle](#) property. However, with this method, you can set any number of days to the same style in one call whereas the [DayStyle](#) property requires a separate call for each date or date range.

The Days parameter is an @FM delimited list of dates or date ranges. For single dates, the field is a single integer representing a single date in OpenInsight's internal format. For date ranges, the field is two integers separated by a dash '-' character. You can supply any combination of single dates or date ranges in any order. All dates in the list will be set to the given style.

Example

```
// Set style to Bold Red
Style = ""
Style<1> = "Red"
Style<3> = @SVM:@SVM:700

// Set a single date followed by a date range
Days = ""
Days<1> = "15250"
Days<2> = "15260-15266"

// Make the call
Send_Message(@Window:"OLE.DATEPICKER", "OLE.SetDayStyles")
```

See Also

[DayStyle](#)