

CellEditMode

Establishes a cell's behavior when selected.

Usage

```
Set_Property(OLECtrlEntID, "OLE.CellEditMode[field; record]", Array)
```

Values

Array has the following structure:

Pos	Name	Type	Description	Default
<1>	Edit Mode	Option	The mode the cell enters when selected	Current
<2>	Cursor Behavior	Option	The location of the cursor when entering edit mode	Overwrite

Indices

Index	Description
field	Index to an existing field
record	Index to an existing record

Remarks

The CellEditMode property establishes how a cell responds to being selected. The first field, Edit Mode, sets whether or not the cell goes immediately into edit mode. Possible values for the Edit Mode field are:

Value	Abbr.	Description
Current	C	The newly selected cell enters the same mode as the previously selected cell
Edit	E	The newly selected cell always enters edit mode
Navigation	N	The newly selected cell never enters edit mode until the user specifically requests to do so

The second field, Cursor Behavior, sets the behavior of the cursor when a cell enters edit mode. Possible values for the Cursor Behavior field are:

Value	Abbr.	Description
Overwrite	O	When entering edit mode, the cell's text is highlighted so typing will overwrite the current contents
Insert	I	When entering edit mode, the cursor is placed at the end of the cell's text so typing will append text to the end