

# CellEditMode

Establishes a cell's behavior when selected.

## Usage

```
Set_Property(OLECtrlEntID, "OLE.CellEditMode[field; record]", Array)
```

## Values

Array has the following structure:

Pos	Name	Type	Description	Default
<1>	Edit Mode	Option	The mode the cell enters when selected	Current
<2>	Cursor Behavior	Option	The location of the cursor when entering edit mode	Overwrite

## Indices

Index	Description
field	Index to an existing field
record	Index to an existing record

## Remarks

The CellEditMode property establishes how a cell responds to being selected. The first field, Edit Mode, sets whether or not the cell goes immediately into edit mode. Possible values for the Edit Mode field are:

Value	Abbr.	Description
Current	C	The newly selected cell enters the same mode as the previously selected cell
Edit	E	The newly selected cell always enters edit mode
Navigation	N	The newly selected cell never enters edit mode until the user specifically requests to do so

The second field, Cursor Behavior, sets the behavior of the cursor when a cell enters edit mode. Possible values for the Cursor Behavior field are:

Value	Abbr.	Description
Overwrite	O	When entering edit mode, the cell's text is highlighted so typing will overwrite the current contents
Insert	I	When entering edit mode, the cursor is placed at the end of the cell's text so typing will append text to the end