

OnHeaderClick

Fired when the user clicks on a header cell.

Parameters

Parameter	Description
HeaderCell	HeaderCell that was clicked
Point	Mouse cursor location relative the control's top left corner
Button	The button pressed during the click
Shift	Indicates whether or not the SHIFT key is down
Ctrl	Indicates whether or not the CTRL key is down

Remarks

The OnHeaderClick event is fired when the user clicks on a header cell.

The HeaderCell parameter indicates the header cell that was clicked on. It contains the column and row location delimited by a semi-colon. For example, double clicking on the top left header cell will return "1;1".

The Point parameter contains the mouse cursors coordinates relative to the upper left corner of the control. It contains the x and y positions delimited by a comma, e.g. "100,100".

The Button parameter indicates the button that is used to fire the click event. This value is "Left" if the left mouse button was pressed, "Middle" if the middle mouse button was pressed, or "Right" if the right mouse button was pressed.

The Shift and Ctrl parameters indicate whether or not the SHIFT or CTRL keys, respectively, were pressed when the event was fired. If either key was pressed, then its corresponding parameter will have a value of 1.

Example

```
Transfer Param1 to HeaderCell
Transfer Param2 to Point
Transfer Param3 to Button
Transfer Param4 to Shift
Transfer Param5 to Ctrl

// Bold the header's font when clicked
Set_Property(@Window:".OLE_EDITTABLE", "OLE.HeaderFont[":HeaderCell:"]", @SVM:@SVM:700)
```

See Also

[OnClick](#), [OnHeaderDbClick](#), [OnHeaderHyperClick](#)