

SelfPos

The list of indexes of the selected rows.

Usage

```
Set_Property(OLECtrlEntID, "OLE.SelfPos", Array)
```

Values

Array has the following structure:

Pos	Name	Type	Description	Default
<1>	Selected Row	Integer	Index to a selected row	""

Remarks

The SelfPos property can be used to get or set the selected rows in the table. The list is always an @FM delimited array of indexes to selected rows. It is empty if there are no selected rows.

If you prefer to get the data of all selected rows, use the [SelList](#) property.

By default, the user can only select one row at a time. To allow multiple selected rows, see the [MultiSelect](#) property.

This property always returns the selection in ascending order. Alternatively, you may use the [SelfPosOrdered](#) property.

Example

```
// Get the list of selected rows
SelfPos = Get_Property(@Window:".OLE_RECORDTABLE", "OLE.SelfPos")

// Set row 7 as the selected row
Set_Property(@Window:".OLE_RECORDTABLE", "OLE.SelfPos", 7)

// Enable multiselect and programmatically set the first 3 rows
Set_Property(@Window:".OLE_RECORDTABLE", "OLE.MultiSelect", 1)
SelfPos = 1:@FM:2:@FM:3
Set_Property(@Window:".OLE_RECORDTABLE", "OLE.SelfPos", SelfPos)
```

See Also

[MultiSelect](#), [SelList](#), [SelfPosOrdered](#)