

# SRP\_Date MonthName

A month's name in a given locale.

```
Name = SRP_Date("MonthName", Month, NameLength = "Full", Locale = "")
```

## Returns

The human readable name for the given month.

## Parameters

Parameter	Description
Month	A month identifier, 1 - 12. <b>(REQUIRED)</b>
NameLength	How the name is to be returned: options are "Full" or "Abbreviated". <i>(OPTIONAL)</i>
Locale	A locale for culture specific names. <i>(OPTIONAL)</i>

## Remarks

The "MonthName" service retrieves the cultural specific name for a given month. The *Month* parameter must be an integer between 1 and 12. The value returned depends on two factors: *NameLength* and *Locale*. *NameLength* can be on of two options: "Full" returns the full name and "Abbreviated" returns the commonly used abbreviation. *Locale* is the [locale name](#) used to target a specific language.

Here is a sample of possible return values if the Month is set to 4. The top row is the *Locale* value and the left column is the *NameLength* value:

	en-US	es-MX	fr-CA
Full	April	abril	avril
Abbreviated	Apr	abr.	avr.

## Examples

```
// Get the full name for September in the local culture
Name = SRP_Date("MonthName", 9)

// Get the abbreviated name for September in the local culture
Name = SRP_Date("MonthName", 9, "Abbreviated")

// Get the abbreviated name for September in Spain
Name = SRP_Date("MonthName", 9, "Abbreviated", "es-ES")
```