

# 3.x - Error\_Services

Error tracking and reporting utility.

## Syntax

```
Response = Error_Services(Service, Param1, Param2, Param3, Param4, Param5, Param6, Param7, Param8, Param9,  
Param10)
```

## Returns

The meaning of the response value depends on the service.

## Parameters

Parameter	Description
Service	The name of the service being requested. <b>Required</b> .
Param1 - Param10	Generic parameters.

## Remarks

This SRP FrameWorks utility service is a general purpose error tracking and reporting utility. Unlike OpenInsight error routines, `Error_Services` does not interfere with normal operations even if a previous error condition was set. The developer is given the right (and responsibility) to make these decisions.

## Services

Service	Description
<b>Set</b>	<b>Usage:</b> <code>Error_Services('Set', ErrorMessage)</code>  <b>Comments:</b> Sets an error to the stack. This will automatically clear any existing error conditions first so this error will be the only one on the stack.  <b>Returns:</b> N/A
<b>Add</b>	<b>Usage:</b> <code>Error_Services('Add', ErrorMessage)</code>  <b>Comments:</b> Adds an error to the stack. This will not clear existing error conditions first. It is intended to allow higher level routines to add more information to an existing error condition or simply to maintain an ongoing error log for some troubleshooting or debugging purposes.  <b>Returns:</b> N/A
<b>Clear</b>	<b>Usage:</b> <code>Error_Services('Clear')</code>  <b>Comments:</b> Clears all error conditions and related information.  <b>Returns:</b> N/A
<b>GetMessage</b>	<b>Usage:</b> <code>Error_Services('GetMessage')</code>  <b>Comments:</b> Returns the most current error message.  <b>Returns:</b> The most current error message.

<b>GetMessages</b>	<p><b>Usage:</b>  <code>Error_Services('GetMessages')</code></p> <p><b>Comments:</b>      Returns the stack of error messages. This will be @FM delimited.</p> <p><b>Returns:</b>      The stack of error messages.</p>
<b>HasError</b>	<p><b>Usage:</b>  <code>Error_Services('HasError')</code></p> <p><b>Comments:</b>      Returns <i>True</i> if there is an error condition, <i>False</i> if there is no error condition. Caller will still need to use the <b>GetMessage</b> or <b>GetMessages</b> service to determine what the error is. The <b>HasError</b> service allows the caller to embed the <a href="#">Error_Services</a> service call inside of a conditional statement like this:</p> <pre>If Error_Services('HasError') then   * An error has occurred. Proceed accordingly.   ErrorMessage = Error_Services('GetMessage') end else   * No error has occurred. end</pre> <p><b>Returns:</b>  <i>True</i> if there is an error condition, <i>False</i> if there is no error condition.</p>
<b>NoError</b>	<p><b>Usage:</b>  <code>Error_Services('NoError')</code></p> <p><b>Comments:</b>      Returns <i>True</i> if there are no error conditions, <i>False</i> if there is an error condition. This is the opposite of the <b>HasError</b> service and exists for improved readability.</p> <p><b>Returns:</b>  <i>True</i> if there are no error conditions, <i>False</i> if there is an error condition.</p>
<b>DisplayError</b>	<p><b>Usage:</b>  <code>Error_Services('DisplayError')</code></p> <p><b>Comments:</b>      Displays the current error message to the end user. <a href="#">Error_Services</a> is designed to avoid any user interface so it can be safe to use in application contexts where no presentation server context is available (e.g., web applications). For convenience, the <b>DisplayError</b> service was added to make it easy to display the most recent error added to the stock.</p> <p><b>Returns:</b>      N/A</p>

## Param1 - Param10

The proper use of the generic arguments are defined in the definition of each service above.