

WebAccounts_Services

Service module to handle Web Accounts interactions.

Syntax

```
Response = WebAccounts_Services(@Service, @Params)
```

Returns

The meaning of the response value depends on the service.

Parameters

Parameter	Description
@Service	The name of the service being requested. Required.
@Params	Generic parameters. Refer to a specific service to determine the actual parameters used.

Remarks

This module provides several useful services for high level interaction with database tables and rows.

Services

Service	Description
GetWebAccounts	Usage: WebAccounts_Services('GetWebAccounts', AccountID, ReturnJSON) Comments: Returns the database row from the WebAccounts table for the indicated Account ID. The default format is MultiValue. Returns: See comments.
SetWebAccounts	Usage: WebAccounts_Services('SetWebAccounts', AccountID, WebAccountsRow) Comments: Updates the WebAccounts database row for the indicated Account ID. Returns: N/A
ConvertMultiValueWebAccountsToJSON	Usage: WebAccounts_Services('ConvertMultiValueWebAccountsToJSON', AccountID, mvWebAccounts, itemURL) Comments: Converts a MultiValue formatted WebAccounts row into a serialized JSON object and returns the result. If the <i>mvWebAccounts</i> argument is empty, the service will attempt to get it from the WebAccounts table. If the itemURL argument is not empty, HAL+JSON properties will be added to the JSON object. Returns: The indicated WebAccount in JSON format.
ConvertJSONWebAccountsToMultiValue	Usage: WebAccounts_Services('ConvertJSONWebAccountsToMV', jsonWebAccounts) Comments: Converts a serialized JSON WebAccounts object into a MultiValue formatted WebAccounts row and returns the result. Returns: The indicated WebAccount in MultiValue format.

Params

The proper use of the generic arguments are defined in the definition of each service above.