

CLICK

Description

Occurs when a user presses, then releases, the mouse button over a control.

Syntax

```
bforward = CLICK (ctrlentID, ctrlclassID)
```

Parameters

CLICK accepts arguments for the following parameters.

Parameter	Description																				
ctrlentID	Has the format <i>WindowName.ControlName</i> , where <i>WindowName</i> is the identifier of the window that contains the affected control, and <i>ControlName</i> is the identifier of the control. Notice that a period separates the two values.																				
ctrlclassID	The type of control that recognizes the event. Valid entries are:																				
	<table><tr><th>Type</th><th>Description</th></tr><tr><td>CHECKBMP</td><td>Check box with a bitmap on it.</td></tr><tr><td>CHECKBOX</td><td>Check box.</td></tr><tr><td>EDITTABLE</td><td>Edit table.</td></tr><tr><td>ICON</td><td>Icon.</td></tr><tr><td>PUSHBMP</td><td>Push-button with a bitmap on it.</td></tr><tr><td>PUSHBUTTON</td><td>Push-button.</td></tr><tr><td>RADIOBMP</td><td>Radio button with a bitmap on it.</td></tr><tr><td>RADIOBUTTON</td><td>Radio button.</td></tr><tr><td>TABCONTROL</td><td>Sets and navigates to the tab which was selected.</td></tr></table>	Type	Description	CHECKBMP	Check box with a bitmap on it.	CHECKBOX	Check box.	EDITTABLE	Edit table.	ICON	Icon.	PUSHBMP	Push-button with a bitmap on it.	PUSHBUTTON	Push-button.	RADIOBMP	Radio button with a bitmap on it.	RADIOBUTTON	Radio button.	TABCONTROL	Sets and navigates to the tab which was selected.
Type	Description																				
CHECKBMP	Check box with a bitmap on it.																				
CHECKBOX	Check box.																				
EDITTABLE	Edit table.																				
ICON	Icon.																				
PUSHBMP	Push-button with a bitmap on it.																				
PUSHBUTTON	Push-button.																				
RADIOBMP	Radio button with a bitmap on it.																				
RADIOBUTTON	Radio button.																				
TABCONTROL	Sets and navigates to the tab which was selected.																				

Returns

True or false. If false, the program execution returns to the calling procedure. If true, then event processing goes to the next level.

Remarks

To determine the clicked row in an edit table, use the [NOTIFYPOS property](#). For the CHECKBMP and CHECKBOX types, use the [CHECK property](#) to get the current state; for the RADIOBUTTON types, use the [VALUE property](#).

See Also

[DBLCLICK event](#), [BUTTONDOWN event](#), [BUTTONUP event](#)