

# CLICK

## Description

Occurs when a user presses, then releases, the mouse button over a control.

## Syntax

*bforward* = **CLICK** (*ctrlentID*, *ctrlclassID*)

## Parameters

CLICK accepts arguments for the following parameters.

Parameter	Description																				
<i>ctrlentID</i>	Has the format <i>WindowName.ControlName</i> , where <i>WindowName</i> is the identifier of the window that contains the affected control, and <i>ControlName</i> is the identifier of the control. Notice that a period separates the two values.																				
<i>ctrlclassID</i>	The type of control that recognizes the event. Valid entries are:																				
	<table><tr><th>Type</th><th>Description</th></tr><tr><td>CHECKBMP</td><td>Check box with a bitmap on it.</td></tr><tr><td>CHECKBOX</td><td>Check box.</td></tr><tr><td>EDITTABLE</td><td>Edit table.</td></tr><tr><td>ICON</td><td>Icon.</td></tr><tr><td>PUSHBMP</td><td>Push-button with a bitmap on it.</td></tr><tr><td>PUSHBUTTON</td><td>Push-button.</td></tr><tr><td>RADIOBMP</td><td>Radio button with a bitmap on it.</td></tr><tr><td>RADIOBUTTON</td><td>Radio button.</td></tr><tr><td>TABCONTROL</td><td>Sets and navigates to the tab which was selected.</td></tr></table>	Type	Description	CHECKBMP	Check box with a bitmap on it.	CHECKBOX	Check box.	EDITTABLE	Edit table.	ICON	Icon.	PUSHBMP	Push-button with a bitmap on it.	PUSHBUTTON	Push-button.	RADIOBMP	Radio button with a bitmap on it.	RADIOBUTTON	Radio button.	TABCONTROL	Sets and navigates to the tab which was selected.
Type	Description																				
CHECKBMP	Check box with a bitmap on it.																				
CHECKBOX	Check box.																				
EDITTABLE	Edit table.																				
ICON	Icon.																				
PUSHBMP	Push-button with a bitmap on it.																				
PUSHBUTTON	Push-button.																				
RADIOBMP	Radio button with a bitmap on it.																				
RADIOBUTTON	Radio button.																				
TABCONTROL	Sets and navigates to the tab which was selected.																				

## Returns

True or false. If false, the program execution returns to the calling procedure. If true, then event processing goes to the next level.

## Remarks

To determine the clicked row in an edit table, use the [NOTIFYPOS property](#). For the CHECKBMP and CHECKBOX types, use the [CHECK property](#) to get the current state; for the RADIOBUTTON types, use the [VALUE property](#).

## See Also

[DBLCLICK event](#), [BUTTONDOWN event](#), [BUTTONUP event](#)