

# DSOSETPARAM

## Description

Passes parameters to the DataSet definition script.

## Syntax

*Syntaxbforward* = **DSOSETPARAM** (*ctrlentID*, *ctrlclassID*, *DSOID*, *paramID*, *paramvalue*)

## Parameters

DSOSETPARAM accepts arguments for the following parameters:

Parameter	Description
<i>CtrlentID</i>	Has the format <i>WindowName.ControlName</i> , where <i>WindowName</i> is the identifier of the window that contains the control effected, and <i>ControlName</i> is the identifier of the control. Notice that a period separates the two values.
<i>ctrlclassID</i>	The type of control that recognized the event. All data entry controls recognize this event.
<i>DSOID</i>	The name of the DataSet, or the ordinal number of the DataSet (its position in the list of DataSets that appears in the Form Designer's <i>Edit Selection Criteria</i> dialog box)
<i>paramID</i>	Substitutable parameter name or ordinal number (if not specified, the parameter this control is bound to is used).
<i>paramvalue</i>	Substitutable parameter value (if not specified, the value of DEFPROP is taken).

## Returns

True or False. If false, program execution returns to the calling procedure. If true, then event processing goes to the next level.

## See also

[DSOEXECUTE](#), [DSOCLEAR](#) events

## Remarks

If a control is bound to a substitutable parameter for a DataSet, the generic [LOSTFOCUS event](#) sends the **DSOSETPARAM event** with an appropriate DSOID, paramID, and paramvalue.