GOTFOCUS

Description

Occurs when focus shifts to the control.

Syntax

bforward = GOTFOCUS (ctrlentID, ctrlclassID, PrevFocusID)

Parameters

GOTFOCUS accepts arguments for the following parameters.

Parameter		
ctrlentID	Has the format WindowName.ControlName, where WindowName is the identifier of the window that contains the affected controlName is the identifier of the control. Notice that a period separates the two values.	
ctrlclassID	The type of control that recognizes the event. Valid entries are:	
	Туре	Description
	CHECKBOX	Check box.
	СОМВОВОХ	Combo box.
	EDITBOX	Edit box.
	EDITFIELD	Edit line.
	EDITTABLE	Edit table.
	LISTBOX	List box.
	PUSHBUTTON	Push-button.
	RADIOBUTTON	Radio button.
	WINDOW	Window.
PrevFocusID	The previous value of the GOTFOCL	

Returns

True or false. If false, the program execution returns to the calling procedure. If true, the event processing goes to the next level.

See also

LOSTFOCUS, ACTIVATED, INACTIVATED events, FOCUS property

Remarks

Set_Property(ctrlentID, 'FOCUS') does not execute this event while Set_Property ('SYSTEM', 'FOCUS', ctrlentID) does.