

# HSCROLL

## Description

Occurs when a window is scrolled horizontally.

## Syntax

*bforward* = **HSCROLL** (*ctrlentID*, *ctrlclassID*, *value*)

## Parameters

HSCROLL accepts arguments for the following parameters.

Parameter	Description						
<i>ctrlentID</i>	Has the format <i>WindowName.ControlName</i> , where <i>WindowName</i> is the identifier of the window that contains the affected control, and <i>ControlName</i> is the identifier of that control. Notice that a period separates the two values.						
<i>ctrlclassID</i>	The type of control. Possible values are:						
	<table><tr><th>Type</th><th>Description</th></tr><tr><td>HSCROLL</td><td>Horizontal scroll bar.</td></tr><tr><td>WINDOW</td><td>Window.</td></tr></table>	Type	Description	HSCROLL	Horizontal scroll bar.	WINDOW	Window.
Type	Description						
HSCROLL	Horizontal scroll bar.						
WINDOW	Window.						
<i>value</i>	New position of the thumb (scroll box). This value is within the designated minimum and maximum value for the scroll bar.						

## Returns

True or false. If false, the program execution returns to the calling procedure. If true, the event processing goes to the next level.

## See also

[HPOSITION](#) property, [VSCROLL](#) event