OMNIEVENT

Description

User-defined event.

Syntax

bforward = **OMNIEVENT** *(ctrlentID, ctrlclassID, MESSAGE, param1, param2, param3, param4)*

Parameters

OMNIEVENT accepts arguments for the following parameters.

<table>
<tr><th>Parameter</th><th>Description</th></tr>
<tr><td>ctrlentID</td><td>Has the format WindowName.ControlName, where WindowName is the identifier of the window that contains the affected control, and ControlName is the identifier of the control. Notice that a period separates the two values.</td></tr>
<tr><td>ctrlclassID</td><td>The type of control that recognizes the event. Valid entries are:</td></tr>
<tr><td></td><td>
<table>
<tr><th>Type</th><th>Description</th></tr>
<tr><td>CHECKBOX</td><td>Check box.</td></tr>
<tr><td>COMBOBOX</td><td>Combo box.</td></tr>
<tr><td>EDITBOX</td><td>Edit box.</td></tr>
<tr><td>EDITFIELD</td><td>Edit line.</td></tr>
<tr><td>EDITTABLE</td><td>Edit table.</td></tr>
<tr><td>HSCROLL</td><td>Horizontal scroll bar.</td></tr>
<tr><td>ICON</td><td>Icon.</td></tr>
<tr><td>LISTBOX</td><td>List box.</td></tr>
<tr><td>PUSHBUTTON</td><td>Push-button.</td></tr>
<tr><td>RADIOBUTTON</td><td>Radio button.</td></tr>
<tr><td>VSCROLL</td><td>Vertical scroll bar.</td></tr>
<tr><td>WINDOW</td><td>Window.</td></tr>
</table>
</td></tr>
<tr><td>MESSAGE</td><td>User-defined.</td></tr>
<tr><td>param1</td><td>User-defined.</td></tr>
<tr><td>param2</td><td>User-defined.</td></tr>
<tr><td>param3</td><td>User-defined.</td></tr>
<tr><td>param4</td><td>User-defined.</td></tr>
</table>

Returns

True or false. If false, the program execution returns to the calling procedure. If true, the event processing goes to the next level.