

OPTIONS

Description

Programmer defined; usually occurs when user selects a menu item or uses an accelerator key combination to get additional information.

Syntax

bforward = **OPTIONS** (*ctrlentID*, *ctrlclassID*)

Parameters

OPTIONS accepts arguments for the following parameters.

Parameter	Description										
<i>ctrlentID</i>	Has the format <i>WindowName.ControlName</i> , where <i>WindowName</i> is the identifier of the window that contains the affected control, and <i>ControlName</i> is the identifier of the control. Notice that a period separates the two values.										
<i>ctrlclassID</i>	The type of control that recognizes the event. Valid entries are:										
	<table><tr><th>Type</th><th>Description</th></tr><tr><td>EDITBOX</td><td>Edit box.</td></tr><tr><td>EDITFIELD</td><td>Edit line.</td></tr><tr><td>EDITTABLE</td><td>Edit table.</td></tr><tr><td>WINDOW</td><td>Window.</td></tr></table>	Type	Description	EDITBOX	Edit box.	EDITFIELD	Edit line.	EDITTABLE	Edit table.	WINDOW	Window.
Type	Description										
EDITBOX	Edit box.										
EDITFIELD	Edit line.										
EDITTABLE	Edit table.										
WINDOW	Window.										

Returns

True or false. If false, the program execution returns to the calling procedure. If true, the event processing goes to the next level.

See also

[Popup function](#), [IXLOOKUP event](#)