

# VSCROLL

## Description

Vertical scroll bar.

## Syntax

*bforward* = **VSCROLL** (*ctrlentID*, *ctrlclassID*, *value*)

## Parameters

VSCROLL accepts arguments for the following parameters.

Parameter	Description						
<i>ctrlentID</i>	Has the format WindowName.ControlName, where WindowName is the identifier of the window that contains the affected control, and ControlName is the identifier of the control. Notice that a period separates the two values.						
<i>ctrlclassID</i>	The type of control. Possible values are:						
	<table><tr><th>Type</th><th>Description</th></tr><tr><td>VSCROLL</td><td>Vertical scroll bar.</td></tr><tr><td>WINDOW</td><td>Window.</td></tr></table>	Type	Description	VSCROLL	Vertical scroll bar.	WINDOW	Window.
Type	Description						
VSCROLL	Vertical scroll bar.						
WINDOW	Window.						
<i>Value</i>	New position of the thumb (scroll box). This value is within the designated minimum and maximum value for the scroll bar.						

## Returns

**True** or **false**. If **false**, then program execution returns to the calling procedure. If **true**, the event processing goes to the next level.

## See also

[HSCROLL event](#), [HPOSITION property](#), [PAGE event](#)

## Remarks

The VSCROLL event is generated for multi-page windows when the page changes.