

DBLCLK

Description

Occurs when a user double-clicks the mouse button over a control.

Syntax

bforward = **DBLCLK** (*ctrlentID*, *ctrlclassID*, *ctrlkey*, *shiftkey*, *mousebutton*)

Parameters

DBLCLK accepts arguments for the following parameters.

Parameter	Description										
<i>ctrlentID</i>	Has the format <i>WindowName.ControlName</i> , where <i>WindowName</i> is the identifier of the window that contains the affected control, and <i>ControlName</i> is the identifier of the control. Notice that a period separates the two values.										
<i>ctrlclassID</i>	The type of control that recognizes the event. Valid entries are: <table><tr><th>Type</th><th>Description</th></tr><tr><td>COMBOBOX</td><td>Combo box.</td></tr><tr><td>EDITTABLE</td><td>Edit table.</td></tr><tr><td>ICON</td><td>Icon.</td></tr><tr><td>LISTBOX</td><td>List box.</td></tr></table>	Type	Description	COMBOBOX	Combo box.	EDITTABLE	Edit table.	ICON	Icon.	LISTBOX	List box.
Type	Description										
COMBOBOX	Combo box.										
EDITTABLE	Edit table.										
ICON	Icon.										
LISTBOX	List box.										
<i>ctrlkey</i>	True (1), if the ctrl key is pressed. False (0), if the ctrl key is not pressed.										
<i>shiftkey</i>	True (1), if the shift key is pressed. False (0), if the shift key is not pressed.										
<i>mousebutton</i>	A "0" indicates that the left or center mouse button was pressed. A "1" indicates that the right button was pressed.										

Returns

True or false. If false, the program execution returns to the calling procedure. If true, the event processing goes to the next level.

See also

[BUTTONDOWN event](#), [BUTTONUP event](#), [CLICK event](#)