

Inet_OI_XML Function

Description

Exports XML data from an OpenInsight table. This function can be called directly, either from an OpenInsight program, or from the Web. If called directly, set the first parameter (**Request**) to null and fill in the other parameters.

Syntax

```
retval = Inet_OI_XML(Request, Cmd, DosFile, Select_Statement, Schema_file, Template_Name, bHideMessages)
```

Parameters

The Inet_OI_XML function has the following parameters:

| Parameters | Description |
|-------------------------|---|
| Request | HTTP-request. Use only if calling from the OECGI gateway. If calling from an OpenInsight directly, set to null. FileName = The name of the OpenInsight table that contains the data to export. |
| <i>Cmd</i> | a valid R/LIST LIST statement, listing the table and fields that should be exported. |
| <i>DosFile</i> | The full path name of the DOS filename to be used. Omit the extension. Inet_OI_XML creates both the .XML and .XSD files. Required. For example, if you enter: DosFile = C:\xmlfiles\customers then Inet_OI_XML creates two files. The XML file will be named C:\xmlfiles\customers.xml , and the XML schema file will be named C:\xmlfiles\customers_schema.xsd . |
| Select_Statement | a valid SELECT statement, used to make a subset of the data to export. Optional, needed only if you wish to filter the data. |
| Schema_File | Name of Schema File. If null, the function will create the schema, if valued will use the schema specified to build the XML file. |
| Template_Name | The name of a saved XML Publisher template that has been previously saved. By providing this parameter, you can run XML exports programmatically. If you are not using a template, set to null. |
| bHideMessages | A boolean value that when true will not display processing messages. |

Returns

a URL indicating the location of the file. If called from an OpenInsight program, the URL is of the form:

```
http://localhost/oixml/DosFile
```

The Inet_OI_XML function creates the XML data file (appending the **.XML** extension) and the schema file (appending the **.XSD** extension) corresponding to the OpenInsight file.

See also

[Inet_Msg\(\)](#), [Inet_Repos\(\)](#), [Inet_Rlist\(\)](#), [Inet_Security\(\)](#), [Inet_Trace\(\)](#), [XML_Importer\(\)](#)

Examples (from BASIC+, non-Web)

```

* export fields from CUSTOMERS table
request = ''
cmd = 'LIST CUSTOMERS COMPANY FNAME LNAME CITY STATE ZIP COUNTRY'
dosfile = 'C:\XMLFILES\CUSTOMERS'
select_statement = ''
template_name = ''
schema_file = ''
hide_messages = 0

retval = inet_oi_xml( request, cmd, dosfile, select_statement, schema_file, template_name, hide_messages)

* restrict export to New Jersey customers
request = ''
cmd = 'LIST CUSTOMERS COMPANY FNAME LNAME CITY STATE ZIP COUNTRY'
dosfile = 'C:\XMLFILES\NJ_CUSTOMERS'
select_statement = 'SELECT CUSTOMERS WITH STATE = "NJ"'
template_name = ''
retval = inet_oi_xml( request, cmd, dosfile, select_statement, template_name)

* export based on parameters stored in PRODUCTS XML Publisher template
request = ''
cmd = ''
dosfile = ''
select_statement = ''
template_name = 'PRODUCTS'
schema_file = ''
hide_messages = 0
retval = inet_oi_xml( request, cmd, dosfile, select_statement, schema_file, template_name, hide_messages)

```

Examples (Web-based)

```

/* to export all fields from the CUSTOMERS table, submit the following from the browser */

http://127.0.0.1/cgi-bin/oecgi.exe/INET_OI_XML?FILENAME=CUSTOMERS

/* to export last name and first name of CUSTOMERS in New Jersey */

http://127.0.0.1/cgi-bin/oecgi.exe/INET_OI_XML?CMD=LIST CUSTOMERS LNAME FNAME WITH STATE = 'NJ'

```