

# Set\_EventStatus Function

## Description

Sets the status of an event forwarded from within an event handler.

## Syntax

*truevalue* = **Set\_EventStatus** (*status*, *code*, *args*)

## Parameters

Parameters associated with Set\_EventStatus are as follows.

Parameter	Description								
<i>Status</i>	The value that you want to set the status to: <table><tr><th>Value</th><th>Description</th></tr><tr><td>-1</td><td>Append a status code to list; if the list is empty, a Failure code is assumed.</td></tr><tr><td>0</td><td>Success.</td></tr><tr><td>1</td><td>Failure.</td></tr></table>	Value	Description	-1	Append a status code to list; if the list is empty, a Failure code is assumed.	0	Success.	1	Failure.
Value	Description								
-1	Append a status code to list; if the list is empty, a Failure code is assumed.								
0	Success.								
1	Failure.								
<i>Code</i>	Contains the code indicating the exact nature of the error. Typically, this is a 3 character alphabetic character followed by a number.								
<i>Args</i>	This contains @FM or @VM-delimited list of arguments associated with the error codes.								

## See also

[Forward\\_Event](#), [Get\\_EventStatus\(\)](#), [Send\\_Event\(\)](#), [Post\\_Event\(\)](#). Also, [OpenInsight Events](#)