

ACCESSPOS

Applies to

Edit table.

Description

Sets or returns the position of the internal cursor in the edit table.

Usage

currentcursorpos = **Get_Property** (*objectname*, "ACCESSPOS")

existingprop = **Set_Property** (*objectname*, "ACCESSPOS" , *newposition*)

Remarks

Pass or return a Column:@FM:Row value, where both column and row are integer values representing ordinal positions.

Using [Set_Property\(\)](#), multiple properties can be set more efficiently in a single call than in multiple calls. The **ACCESSPOS** and [ACCESSDATA](#) properties can be set multiple times in a single call to set the values of multiple cells. The following example sets the first and third cell of the first row:

```
Ctrls = CtrlEntID:@RM:CtrlEntID:@RM:CtrlEntID:@RM:CtrlEntID
Props = "ACCESSPOS":@RM:"ACCESSDATA":@RM:"ACCESSPOS":@RM|
        "ACCESSDATA"
Vals = 1:@FM:1:@RM: Name :@RM: 3:@FM:1 :@RM: Phone_Number
Set_Property (Ctrls, Props, Vals)
```

Returns

Values returned by both Get_Property and Set_Property

Value	Description
<i>currentcursorpos</i>	Data at the current internal cursor position.
<i>existingprop</i>	Position of the internal cursor, when Set_Property was called.

See also

[ACCESSDATA](#) property, [CARETPOS](#) property, [CELLPOS](#) property, [CLICKPOS](#) property, [NOTIFYPOS](#) property, [SELPOS](#) property