

DRAGCOPY

Applies to

Drag Source controls

Description

A boolean property denoting if a drag source control allows a copy operation

Usage

dragCopy = **Get_Property** (*dragSource*, "DRAGCOPY")

existingState = **Set_Property** (*dragSource*, "DRAGCOPY", *bValue*)

Remarks

Values passed in Set_Property():

Value	Description
<i>bValue</i>	Boolean true (1) or false (0)

By default the DRAGCOPY property is set to 1. This property should be set during the DRAGSTART event when overriding the default property. The DRAGMOVE property overrides the DRAGCOPY property. If you have both the DRAGMOVE and DRAGCOPY properties set to 1 then the DRAGMOVE will occur not the DRAGCOPY.

Returns

Values returned by Get_Property and Set_Property

Value	Description
<i>dragCopy</i>	the Boolean status of the control's DRAGCOPY.
<i>existingState</i>	the Boolean status of the control's DRAGCOPY, when Set_Property was run.

See Also

[DRAGSOURCE property](#), [DRAGMOVE property](#)

Example

```
Declare function Get_Property, Set_Property

* Turn the DRAGCOPY property off.

dragSource = Get_Property("SYSTEM", "DRAGSOURCE")
dragCopy = Set_Property(dragSource, "DRAGCOPY", 0)
```