

GRADIENTSTYLE

Applies to

Windows

Description

Sets and retrieves the gradient style of the background color of a window.

Usage

gradient = **Get_Property** (*objectname*, "GRADIENTSTYLE")

currentStyle = **Set_Property** (*objectname*, "GRADIENTSTYLE", *gValue*)

Remarks

Values passed in Set_Property():

Value	Description												
<i>gValue</i>	An integer value denoting one of the following gradient styles: <table><tr><th>Value</th><th>Gradient Style</th></tr><tr><td>1</td><td>Vertical (default)</td></tr><tr><td>2</td><td>Horizontal</td></tr><tr><td>3</td><td>Ellipse</td></tr><tr><td>4</td><td>Pyramid (rectangle)</td></tr><tr><td>5</td><td>Mount (round rectangle)</td></tr></table>	Value	Gradient Style	1	Vertical (default)	2	Horizontal	3	Ellipse	4	Pyramid (rectangle)	5	Mount (round rectangle)
Value	Gradient Style												
1	Vertical (default)												
2	Horizontal												
3	Ellipse												
4	Pyramid (rectangle)												
5	Mount (round rectangle)												

Note: The background color must be set and the Background Color checkbox in the Window's Property Dialog must be checked.

Returns

Values returned by Get_Property and Set_Property

Value	Description
<i>gradient</i>	The current value of the window's gradient style.
<i>existingGradient</i>	The window's gradient style prior to the setting of the style.

See Also

[BACKCOLOR property](#), [FORECOLOR property](#), [CHOOSECOLOR Utility\(\) service](#)

Example

```
Declare function Set_Property

$Insert Colors
equ Vertical$ to 1

vBackColor = Red$ : @fm : Black$ : @fm : 0
prevBack = Set_Property(@window, "BACKCOLOR", vBackColor)
prevGrad = Set_Property(@window, "GRADIENTSTYLE", Vertical$)
```