

Update_Index Subroutine

Description

Updates or rebuilds indexes in a specified column or for all columns in an attached table.

Syntax

Update_Index (*table_name*, *column_name*, *rebuildflag*)

Parameters

Parameters are as follows.

| Parameter | Description |
|--------------------|--|
| <i>table_name</i> | The name of the table whose indexes are updated or rebuilt. If <i>table_name</i> is null, and <i>rebuildflag</i> is false (0) or null, all indexes for all attached tables are updated. |
| <i>column_name</i> | Update or rebuild all indexes for the specified column. If <i>column_name</i> is null, and <i>rebuildflag</i> is false (0) or null, all indexes for <i>table_name</i> are updated. If <i>column_name</i> is null, and <i>rebuildflag</i> is True (1), all indexes for <i>table_name</i> are rebuilt. |
| <i>rebuildflag</i> | If <i>rebuildflag</i> is true (1), indexes are rebuilt. |

The *table_name* contains a system delimiter.

See also

[Create_Index](#), [Delete_Index](#), [List_Index](#)

Example

```
/* Updates the index on the PART_NAME column in the CAR_PARTS table. */
Call Update_Index ("CAR_PARTS", "PART_NAME", "")
/* Rebuilds indexes on the PART_NAME column in the CAR_PARTS table. */
Call Update_Index ("CAR_PARTS", "PART_NAME", "1")
```