

# FONT BY POS

## Description

Set the font for the text of the specified item. Item is specified either by position or by (column, row) coordinates (for an edit table control).

## Applies to

Edit table.

## Syntax

```
text = Send_Message(controlID, "FONT_BY_POS", column, row, fontstructure)
```

## Parameters

For FONT\_BY\_POS, the Send\_Message function has the following parameters.

Parameter	Description
column, row	When column and row are both positive, applies the fontstructure to the cell; when column is positive and row is 0, applies fontstructure to the entire column; when column is 0 and row is positive applies the fontstructure to the entire row. When the column is positive and row is -1 the row button font is set. When the row is positive and the column is set to -1 the column header font is set.
Fontstructure	An @SVM-delimited array. (Refer to the <a href="#">FONT property</a> in <a href="#">Chapter 4: Properties</a> .)

## See also

[FONT property](#), [Utility \("CHOOSEFONT"\)](#)

## Examples

```
/* Set the header in column 1 to desired FONT scheme */
rv = Send_Message(@Window:".TABLE_3", "FONT_BY_POS", 1, -1, "Times New Roman")
/* Set the 5th row's button font to Helvetica */
rv = Send_Message(@Window:".TABLE_3", "FONT_BY_POS", -1, 5, "Helvetica")
```