

REMOVEDRAGDATA

Description

This message is used to remove the specified data format from the dragged data.

Syntax

```
RetVal = Send_Message(ctrlEntId, "REMOVEDRAGDATA", format)
```

Parameters

The function has the following parameters:

Parameters	Description									
ctrlEntID	Must be a current drag source control.									
format	Name of the format you want to clear. This can be a custom format or one of the following standard OpenInsight data formats. <table border="1"><thead><tr><th>Format</th><th>Description</th></tr></thead><tbody><tr><td>TEXT</td><td>Sets textual data in both ANSI and Unicode format.</td></tr><tr><td>FILENAME</td><td>Sets a filename data format.</td></tr><tr><td>BITMAP</td><td>Sets BITMAP, a bit dta format. The data should be a bitmap path.</td></tr></tbody></table>		Format	Description	TEXT	Sets textual data in both ANSI and Unicode format.	FILENAME	Sets a filename data format.	BITMAP	Sets BITMAP, a bit dta format. The data should be a bitmap path.
Format	Description									
TEXT	Sets textual data in both ANSI and Unicode format.									
FILENAME	Sets a filename data format.									
BITMAP	Sets BITMAP, a bit dta format. The data should be a bitmap path.									

Returns

A boolean value. TRUE for successful, FALSE if unsuccessful.

Remarks

The message can only be used during the DRAGSTART event for drag source control. This effectively cancels all current drag activity.

See also

[DRAGSOURCE property](#), [DROPTARGET property](#), [SETDRAGDATA message](#), [CLEARDRAGDATA message](#), [GETDRAGDATA message](#)

Example

```
* Change the "TEXT" data being dragged
dragSource = Get_Property("SYSTEM", "DRAGSOURCE")
data = Send_Message(dragSource, "GETDRAGDATA", "TEXT", "", "")
if data _eqc 'Rutherford B. Hayes' then
  data = Send_Message(dragSource, "REMOVEDRAGDATA", "TEXT")
end
```