

SETDRAGDATA

Description

This message is used to set the data for a dragged data object

Syntax

```
retVal = Send_Message(ctrlEntId,"SETDRAGDATA",format,unicode,data)
```

Parameters

The function has the following parameters:

Parameters	Description								
ctrlEntID	Must be a current drag source control.								
format	Name of the format you want to set. This can be a custom format or one of the following standard OpenInsight data formats. <table><tr><th>Format</th><th>Description</th></tr><tr><td>TEXT</td><td>Sets textual data in both ANSI and Unicode format.</td></tr><tr><td>FILENAME</td><td>Sets a filename data format.</td></tr><tr><td>BITMAP</td><td>Sets BITMAP, a bit dta format. The data should be a bitmap path.</td></tr></table>	Format	Description	TEXT	Sets textual data in both ANSI and Unicode format.	FILENAME	Sets a filename data format.	BITMAP	Sets BITMAP, a bit dta format. The data should be a bitmap path.
Format	Description								
TEXT	Sets textual data in both ANSI and Unicode format.								
FILENAME	Sets a filename data format.								
BITMAP	Sets BITMAP, a bit dta format. The data should be a bitmap path.								
unicode	When using a custom textual format, set this flag to true for OpenInsight to perform a Unicode to UTF8/ANSI translation automatically if you know the data is Unicode string.								
data	The data to be set.								

Returns

A boolean value. TRUE for successful, FALSE if unsuccessful.

Remarks

The message can only be used during the DRAGSTART event for drag source control.

See also

[DRAGSOURCE property](#), [DROPTARGET property](#), [CLEARDRAGDATA message](#), [REMOVEDRAGDATA message](#), [GETDRAGDATA message](#)

Example

```
* Change the "TEXT" data being dragged
dragSource = Get_Property("SYSTEM","DRAGSOURCE")
data = Send_Message(dragSource,"GETDRAGDATA","TEXT","","")
if data _eqc 'Woodrow Wilson' then
    newData = "Theodore Roosevelt"
    data = Send_Message(dragSource,"SETDRAGDATA","TEXT","",newData)
end
```