

SUPPRESSKEYTRANSLATE

Description

This message provides for [NOACCELTRANSLATION property](#) functionality for specific keystrokes within an OLE/OCX control. When the SUPPRESSKEYTRANSLATE is turned on the passing of an OLE control's keystroke processing to the OpenInsight Presentation Server is stopped.

Syntax

```
retval = Send_Message(oleControl, "SUPPRESSKEYTRANSLATE", keystroke, bValue)
```

Parameters

The function has the following parameters:

Parameters	Description
oleControl	The fully qualified control identifier for the OLE/OCX control.
keystroke	The virtual key code to suppress
bValue	If true then the keystroke will be suppressed, if false then the keystroke will not be suppressed.

Returns

The previous bValue of the SUPPRESSKEYTRANSLATE property for the keystroke within the control.

See also

[NOACCELTRANSLATION property](#), [FORCEKEYDISPATCH message](#)

Version

Introduced in OpenInsight version 8.0.5.

Example

```
* This example will stop the BACKSPACE key from being processed by the OpenInsight
* Presentation Server but all other keys will be processed by OpenInsight.

equ VK_BACK$ to 8
oleControl = @window : ".OLECONTROL_1"
prevKeyVal = Send_Message( oleControl, "SUPPRESSKEYTRANSLATE", VK_BACK$, TRUE$)
```