

IXLOOKUP

Description

Looks up index.

Syntax

bforward = **IXLOOKUP** (*ctrlentID*, *ctrlclassID*, *indexedtable*, *searchcolumns*, *displaycolumns*, *selmode*)

Parameters

IXLOOKUP accepts arguments for the following parameters.

Parameter	Description								
<i>ctrlentID</i>	Has the format <i>WindowName.ControlName</i> , where <i>WindowName</i> is the identifier of the window that contains the affected control, and <i>ControlName</i> is the identifier of the control. Notice that a period separates the two values.								
<i>ctrlclassID</i>	The type of control that recognizes the event. The window control is the only valid entry.								
<i>indexedtable</i>	The table containing Btree index(es).								
<i>searchcolumns</i>	The indexed columns to search delimited by @FM.								
<i>displaycolumns</i>	The columns to display in the resultant popup, delimited by @FM.								
<i>selmode</i>	The selection mode delimited by @FM.								
	<table><tr><th>Value</th><th>Description</th></tr><tr><td>Field 1</td><td>MULTI or SINGLE. If null, then SINGLE.</td></tr><tr><td>Field 2</td><td>Control to return popup result to. If null, then whatever control is specified. The default is QBFLIST.</td></tr><tr><td>Field 3</td><td>Control property to set. Generally TEXT.</td></tr></table>	Value	Description	Field 1	MULTI or SINGLE. If null, then SINGLE.	Field 2	Control to return popup result to. If null, then whatever control is specified. The default is QBFLIST.	Field 3	Control property to set. Generally TEXT .
Value	Description								
Field 1	MULTI or SINGLE. If null, then SINGLE.								
Field 2	Control to return popup result to. If null, then whatever control is specified. The default is QBFLIST.								
Field 3	Control property to set. Generally TEXT .								

Returns

True or false. If false, the program execution returns to the calling procedure. If true, the event processing goes to the next level.

See also

[QBFLIST](#) property