

RUNHELP Service

Description

Passes *<object>* as a help file name to the Windows WinHelp() function. The WinHelp () function starts Windows Help and passes optional data indicating the nature of the help requested by the application.

Parameters

| Parameter | Description |
|----------------------|---|
| <i><value></i> | (Optional.) An @FM-delimited array: |
| | <1> Owner window name |
| | <2> Command (second parameter for WinHelp) |
| | <3> extra Parameter (polymorphic third parameter for WinHelp) |
| <i>Returnvalue</i> | Nonzero if the function is successful. Zero if the function was not successful. |

Example

```
/* runs the Windows Help 1.0 file NTHELP.HLP */
declare function utility
foo = utility ("RUNHELP", "NTHELP.HLP")
```

Remarks

Refer to the Windows SDK manual for additional information about the WinHelp() function.

See Also

| Name |
|--|
| BEEP Service |
| CHOOSECOLOR Service |
| CHOOSEDIR Service |
| CHOOSEFILE Service |
| CHOOSEFONT Service |
| COPYFILE Service |
| CREATE Service |
| CURSOR Service |
| DESTROY Service |
| FLUSH Service |
| GET_EVENT Service |
| GETLOGICALDRIVES Service |
| MAKEDIR Service |
| OBJECTID Service |
| OBJECTLIST Service |
| PRINTSETUP Service |
| REMOVEDIR Service |

| |
|--------------------------|
| RENAMEDIR Service |
| RENAMEFILE Service |
| RUNWIN Service |
| TEXTRECT Service |
| WINCOUNT Service |
| HANDLE_BY_CURSOR Service |
| IUNKNOWN_RELEASE Service |
| LOAD_PICTURE Service |
| OBJECT_BY_CURSOR Service |
| PICTURE_PROPS Service |