

Repository Function COPY

Description

Method for copying entities.

Syntax

```
retval = Repository("COPY", entID, destination, source)
```

Parameters

The COPY method has the following parameters

Parameter	Description
Message	COPY
destination	The name of the entity to be created from the copy. The name should be the fully qualified repository id.
source	The entity that will be copied. The name should be the fully qualified repository id.

Returns

Use [Get_Status\(\)](#) to test for error return.

Note: Always call the [Get_Status function](#) after calling [Repository\(\)](#).

Remarks

The fully qualified Repository Id consists of four elements, which are '*' (asterisk) delimited:

- Application name
- Type ID
- Class ID
- Entity name

Methods are executed as follows: if class specific, execute at the class level; if type specific, execute at the type level; otherwise, execute the method.

See also

[Repository\(\) function](#), [Get_Repos_Entities\(\)](#).

Example

```
/* Copy the source code of the CENTERWINDOW stored procedure to CENTERWINDOW_BACKUP */
Declare Function Get_Repos_Entities, Repository, Get_Status
AppID = @APPID<1> ;* current application
TypeID = "STPROC" ;* OpenInsight stored procedures
ClassID = "" ;* Not Applicable
Stored_Proc_Name = 'CENTERWINDOW'
Backup_Proc_Name = 'CENTERWINDOW_BACKUP'
entid = AppID : '*' : TypeID : '*' : ClassID : '*' : Stored_Proc_Name
backupid = AppID : '*' : TypeID : '*' : ClassID : '*' : Backup_Proc_Name
result = Repository("COPY", backupid, entid)
* test result
If Get_Status(ErrCode) then
    call msg(@window, 'Error Message returned: ' : ErrCode)
end
```