

Repository Function GETACCESSPERMIT

Description

Method for getting the users who have access (i.e. reading) permission for this entity.

Syntax

```
retval = Repository('GETACCESSPERMIT', entID)
```

Parameters

The **GETACCESSPERMIT** method has the following parameters.

Parameter	Description
Message	GETACCESSPERMIT
entID	entID consists of four elements, which are '*' (asterisk) delimited: <ul style="list-style-type: none">• Application name• Type ID• Class ID• Entity name
	Methods are executed as follows: if class specific, execute at the class level; if type specific, execute at the type level; otherwise, execute the method.

Returns

A field mark delimited list of users with access permission to this entity.

Note: Always call the [Get_Status function](#) after calling Repository.

See also

[Repository\(\) function](#), [SETACCESSPERMIT Method](#), [Get_Repos_Entities\(\)](#).

Example

```
/* Get the list of users with access permission for the CENTERWINDOW stored procedure into the variable called
result */
Declare Function Get_Repos_Entities, Repository, Get_Status
AppID = @APPID<1> /* current application
TypeID = "STPROC" /* OpenInsight stored procedures
ClassID = "" /* Not Applicable
Stored_Proc_Name = 'CENTERWINDOW'
entid = AppID : '*' : TypeID : '*' : ClassID : '*' : Stored_Proc_Name
result = Repository("GETACCESSPERMIT", entid)
/* result now contains a field mark delimited list of users who have access permission to CENTERWINDOW in
Field 1. */
If Get_Status(ErrCode) then
  call msg(@window, 'Error Message returned: ' : ErrCode)
end
```