

Repository Function GETDOCUMENT

Description

Method for getting the document(s) associated with this entity.

Syntax

```
retval = Repository("GETDOCUMENT" , entID)
```

Parameters

The **GETDOCUMENT** method has the following parameters.

Parameter	Description
<i>Message</i>	"GETDOCUMENT"
<i>entID</i>	<i>entID</i> consists of four elements, which are '*' (asterisk) delimited:
	<ul style="list-style-type: none">• Application name• Type ID• Class ID• Entity name
	Methods are executed as follows: if class specific, execute at the class level; if type specific, execute at the type level; otherwise, execute the method.

Returns

A field mark delimited array of document(s) associated with this entity. This can be accessed from [Entity...Properties...Document](#) in the Repository outline when the entity is highlighted.

Note: Always call the [Get_Status](#) function after calling Repository.

See also

[Repository\(\)](#) function, [Get_Repos_Entities\(\)](#).

Example

```
/* Get the document IDs of the CENTERWINDOW stored procedure into the variable called result */
Declare Function Get_Repos_Entities, Repository, Get_Status
AppID = @APPID<1>  /* current application
TypeID = "STPROC"  /* OpenInsight stored procedures
ClassID = ""      /* Not Applicable
Stored_Proc_Name = 'CENTERWINDOW'
entid = AppID : '*' : TypeID : '*' : ClassID : '*' : Stored_Proc_Name
result = Repository("GETDOCUMENT", entid)
/* result now contains a field mark delimited list of documents associated with CENTERWINDOW */
If Get_Status(ErrCode) then
    call msg(@window, 'Error Message returned: ' : ErrCode)
end
```