

Repository Function GETRECOMPILE

Description

Method for getting the recompilation flag for an entity.

Syntax

retval = **Repository**("GETRECOMPILE" , *entID*)

Parameters

The **GETRECOMPILE** method has the following parameters.

Parameter	Description
<i>Message</i>	"GETRECOMPILE"
<i>entID</i>	<i>entID</i> consists of four elements, which are '*' (asterisk) delimited:
	• Application name • Type ID • Class ID • Entity name
	Methods are executed as follows: if class specific, execute at the class level; if type specific, execute at the type level; otherwise, execute the method.

Returns

A boolean flag (0 = recompile flag off; 1 = recompile flag is on)

Note: Always call the [Get_Status function](#) after calling Repository.

See also

[Repository\(\)](#) function, [Get_Repos_Entities\(\)](#).

Example

```
/* Get the recompile flag or the CENTERWINDOW stored procedure into the variable called result */
Declare Function Get_Repos_Entities, Repository, Get_Status
AppID = @APPID<1>  ;* current application
TypeID = "STPROC"  ;* OpenInsight stored procedures
ClassID = ""       ;* Not Applicable
Stored_Proc_Name = 'CENTERWINDOW'
entid = AppID : '*' : TypeID : '*' : ClassID : '*' : Stored_Proc_Name

result = Repository("GETRECOMPILE", entid)
/* result now contains the publishable flag of CENTERWINDOW */
If Get_Status(ErrCode) then
    call msg(@window, 'Error Message returned: ' : ErrCode)
end
```