

Repository Function GETSUPER

Description

Method for getting a list of "super-entities" (entities used by entID).

Syntax

```
retval = Repository("GETSUPER", entID)
```

Parameters

The **GETSUPER** method has the following parameters.

| Parameter | Description |
|-----------|--|
| Message | "GETSUPER" |
| entID | entID consists of four elements, which are '*' (asterisk) delimited: <ul style="list-style-type: none">• Application name• Type ID• Class ID• Entity name |
| | Methods are executed as follows: if class specific, execute at the class level; if type specific, execute at the type level; otherwise, execute the method. |

Returns

A field mark delimited list of entities used by entid.

Note: Always call the [Get_Status function](#) after calling Repository.

See also

[Repository\(\) function](#), [SETSUPER Method](#), [Get_Repos_Entities\(\)](#).

Example

```
/* Return entities "super" (parent) to the CENTERWINDOW stored procedure into the variable called result */
Declare Function Get_Repos_Entities, Repository, Get_Status
AppID = @APPID<1> /* current application
TypeID = "STPROC" /* OpenInsight stored procedures
ClassID = "" /* Not Applicable
Stored_Proc_Name = 'CENTERWINDOW'
entid = AppID : '*' : TypeID : '*' : ClassID : '*' : Stored_Proc_Name

result = Repository("GETSUPER", entid)
/* result now contains a field mark delimited list of entities super (parent) to the CENTERWINDOW stored
procedure.
For a stored procedure this would be the stored procedure executable (STPROCEXE), if the stored procedure has
been compiled. */
If Get_Status(ErrCode) then
    call msg(@window, 'Error Message returned: ' : ErrCode)
end
```