

Repository Function GETTITLE

Description

Method for getting the entity's title in the repository.

Syntax

```
retval = Repository("GETTITLE" , entID)
```

Parameters

The **GETTITLE** method has the following parameters.

Parameter	Description
<i>Message</i>	"GETTITLE"
<i>entID</i>	<i>entID</i> consists of four elements, which are '*' (asterisk) delimited:
	<ul style="list-style-type: none">• Application name• Type ID• Class ID• Entity name
	Methods are executed as follows: if class specific, execute at the class level; if type specific, execute at the type level; otherwise, execute the method.

Returns

The title of the entity in the repository.

Note: Always call the [Get_Status function](#) after calling Repository.

See also

[Repository\(\)](#) function, [SETTITLE Method](#), [Get_Repos_Entities\(\)](#).

Example

```
/* Get the title for the CENTERWINDOW stored procedure into the variable called result */
Declare Function Get_Repos_Entities, Repository, Get_Status
AppID = @APPID<1>  /* current application
TypeID = "STPROC"  /* OpenInsight stored procedures
ClassID = ""      /* Not Applicable
Stored_Proc_Name = 'CENTERWINDOW'
entid = AppID : '*' : TypeID : '*' : ClassID : '*' : Stored_Proc_Name

result = Repository("GETTITLE", entid)
/* result now contains the title of CENTERWINDOW. */
If Get_Status(ErrCode) then
    call msg(@window, 'Error Message returned: ' : ErrCode)
end
```