

# Repository Function SETPUBLISHABLE

## Description

Method for changing an entity's publishable flag in the repository.

## Syntax

```
retval = Repository("SETPUBLISHABLE", entID)
```

## Parameters

The **SETPUBLISHABLE** method has the following parameters.

Parameter	Description
Message	"SETPUBLISHABLE"
entID	entID consists of four elements, which are '*' (asterisk) delimited: <ul style="list-style-type: none"><li>• Application name</li><li>• Type ID</li><li>• Class ID</li><li>• Entity name</li></ul>
	Methods are executed as follows: if class specific, execute at the class level; if type specific, execute at the type level; otherwise, execute the method.
param1	publishable flag to set (0 = on, 1 = off)

## Returns

Null in all cases.

**Note:** Always call the [Get\\_Status function](#) after calling Repository.

## See also

[Repository\(\) function](#), [GETPUBLISHABLE Method](#), [Get\\_Repos\\_Entities\(\)](#).

## Example

```
/* Set the publishable flag for the for the CENTERWINDOW stored procedure */
Declare Function Repository, Get_Status
AppID = @APPID<1> /* current application
TypeID = "STPROC&EXE" /* OpenInsight stored procedure executable
ClassID = "" /* Not Applicable
Stored_Proc_Name = 'CENTERWINDOW'
flag = '1'
entid = AppID : '*' : TypeID : '*' : ClassID : '*' : Stored_Proc_Name

result = Repository("SETPUBLISHABLE", entid, flag)
/* Even if the publishable flag is set, result is null, so need to check for errors */
If Get_Status(ErrCode) then
  call msg(@window, 'SETPUBLISHABLE method error ' : ErrCode : '.')
  return 1
end
```