

Repository Function SETSHAREABLE

Description

Method for setting the entity's shareable flag in the repository.

Syntax

```
retval = Repository("SETSHAREABLE", entID, param1)
```

Parameters

The 'SETSHAREABLE' method has the following parameters.

Parameter	Description
Message	"SETSHAREABLE"
entID	entID consists of four elements, which are '*' (asterisk) delimited: <ul style="list-style-type: none">• Application name• Type ID• Class ID• Entity name
	Methods are executed as follows: if class specific, execute at the class level; if type specific, execute at the type level; otherwise, execute the method.
param1	Shareable flag to set. 0 = shareable flag disabled; 1 = shareable flag enabled.

Returns

Null, regardless of whether the function succeeded.

Note: Always call the [Get_Status function](#) after calling Repository.

See also

[Repository\(\) function](#), [GETSHAREABLE Method](#), [Get_Repos_Entities\(\)](#).

Example

```
/* Set the shareable flag for the for the BTREEREADTEST window executable */
Declare Function Repository, Get_Status
AppID = @APPID<1> ;* current application
TypeID = "OIWINEXE" ;* OpenInsight window executable
ClassID = "" ;* Not Applicable
Stored_Proc_Name = 'BTREEREADTEST'
flag = '1'
entid = AppID : '*' : TypeID : '*' : ClassID : '*' : Stored_Proc_Name

result = Repository("SETSHAREABLE", entid, flag)
/* Even if the publishable flag is set, result is null, so need to check for errors */
If Get_Status(ErrCode) then
  call msg(@window, 'SETSHAREABLE method error ' : ErrCode : '.')
  return 1
end
```