

Repository Function SETSUBKEY

Description

Method for changing the entity's sub-key in the repository. The sub-key is displayed in the [Entity Relationships browser](#) from the Repository outline menu.

Syntax

```
retval = Repository("SETSUBKEY" , entID)
```

Parameters

The **SETSUBKEY** method has the following parameters.

Parameter	Description
<i>Message</i>	"SETSUBKEY"
<i>entID</i>	<i>entID</i> consists of four elements, which are '*' (asterisk) delimited:
	• Application name • Type ID • Class ID • Entity name
	Methods are executed as follows: if class specific, execute at the class level; if type specific, execute at the type level; otherwise, execute the method.
<i>param1</i>	the sub-key value to store in the repository for this entity.

Returns

Null in all cases.

Note: Always call the [Get_Status function](#) after calling **Repository**.

See also

[Repository\(\)](#) function, [GETSUBKEY Method](#), [Get_Repos_Entities\(\)](#).

Example

```
/* Change the path for the INET_INVOICE_RPT HTML document, stored in the SUB-KEY. */
Declare Function Repository, Get_Status
AppID = @APPID<1> ;* current application
TypeID = "DOC" ;* ;* document type
ClassID = "HTML" ;* HTML class
Report_Name = 'INET_INVOICE_RPT'
New_Sub_Key = '..\HTML\NEWREPORT.HTM'
entid = AppID : '*' : TypeID : '*' : ClassID : '*' : Report_Name

result = Repository("SETSUBKEY", entid, New_Sub_Key)
/* The sub key should be changed in the repository. Result is null, so test for errors. */
If Get_Status(ErrCode) then
    call msg(@window, 'SETSUBKEY Error Message returned: ' : ErrCode)
    return 1
end
```