

Repository Function SETTITLE

Description

Method for setting the entity's title in the repository.

Syntax

```
retval = Repository("SETTITLE" , entID, param1)
```

Parameters

The **SETTITLE** method has the following parameters.

Parameter	Description
<i>Message</i>	"SETTITLE"
<i>entID</i>	<i>entID</i> consists of four elements, which are '*' (asterisk) delimited:
	<ul style="list-style-type: none">• Application name• Type ID• Class ID• Entity name
	Methods are executed as follows: if class specific, execute at the class level; if type specific, execute at the type level; otherwise, execute the method.
<i>param1</i>	The new title for the entity in the repository.

Returns

Null, regardless of whether the function succeeded.

Note: Always call the [Get_Status function](#) after calling Repository.

See also

[Repository\(\) function](#), [GETTITLE Method](#), [Get_Repos_Entities\(\)](#).

Example

```
/* Change the title for the CENTERWINDOW stored procedure */
Declare Function Get_Repos_Entities, Repository, Get_Status
AppID = @APPID<1>  /* current application
TypeID = "STPROC"  /* OpenInsight stored procedures
ClassID = ""      /* Not Applicable
Stored_Proc_Name = 'CENTERWINDOW'
NewTitle = 'A procedure to center a window relative to the desktop.'

entid = AppID : '*' : TypeID : '*' : ClassID : '*' : Stored_Proc_Name
result = Repository("SETTITLE", entid, NewTitle)
/* if successful, title is changed, result is null */
If Get_Status(ErrCode) then
    call msg(@window, 'Error Message returned: ' : ErrCode)
end
```