

Repository Function TDESTROY

Description

Method for destroying entities and entities used by this entity (such as a window and events created in the window). Tdestroying a Window will destroy the window and events. Tdestroying a compiled window will destroy the window events and their compiled versions. Tdestroying a stored procedure executable (**STPROCEXE**) will destroy the source (**STPROC**) and debug (**STPROCDBG**) also.

Syntax

object = **Repository**("TDESTROY" , *entID*)

Parameters

The **TDESTROY** method has the following parameters.

| Parameter | Description |
|----------------|---|
| <i>Message</i> | "TDESTROY" |
| <i>entID</i> | <i>entID</i> consists of four elements, which are '*' (asterisk) delimited: |
| | <ul style="list-style-type: none">• Application name• Type ID• Class ID• Entity name |
| | Methods are executed as follows: if class specific, execute at the class level; if type specific, execute at the type level; otherwise, execute the method. |

Returns

null

Note: Always call the [Get_Status function](#) after calling **Repository**.

See also

[Repository\(\)](#) function, [DESTROY](#) method, [Get_Repos_Entities\(\)](#).

Example

```
* Destroy the BTREEREADTEST_BACKUP form, and entities used by it (window events) */
Declare Function Repository, Get_Status
AppID = @APPID<1>  /* current application
TypeID = "OIWINEXE" /* OpenInsight window executable
ClassID = ""      /* Not Applicable
Window_Name = 'BTREEREADTEST_BACKUP'
entid = AppID : '*' : TypeID : '*' : ClassID : '*' : Window_Name
result = Repository("TDESTROY", entid)
/* the form and its associated events have been destroyed */
* test result
If Get_Status(ErrCode) then
    call msg(@window, 'Error Message returned: ' : ErrCode)
end
```